



PRODUCT CATALOGUE



TABLE OF CONTENTS

MULTI-PURPOSE LUBRICANTS CX80

• multi-purpose lubricant	2
• multi-purpose lubricant with TEFLON®	3

GREASES CX80

• copper grease	4
• lithium grease	5
• CERACX grease	6
• molybdenum grease	7
• silicone grease	8
• graphite grease	9
• bearing grease	10
• waterproof grease	11
• MOTO CHAIN	12
• white grease – solid	13
• ELECTRICX grease	14
• KERAMICX grease	15
• TOWOCX grease	16
• lubricant for gates	17
• silicone spray	18

HIGH TEMPERATURE SILICONES CX80

• professional silicone	19
• professional eco silicone	20

SILICONES CX80

• sanitary silicone	21
• superfast sanitary silicone	22
• multi-purpose silicone	23
• building silicone	24
• neutral silicone	25

SEALANTS CX80

• fireplace sealant	26
---------------------	----

CYANOACRYLATE ADHESIVES CX80

• BONDICX 01	27
• BONDICX 06	28
• BONDICX 05	29
• BONDICX 96	30
• BONDICX 20	31
• BONDICX gel	32
• BONDICX 48	33
• BONDICX 60	34

ANAEROBIC ADHESIVES CX80

• RC 20G	35
• RC 22	36
• RC 38	37

• RC 41	38
• RC 42	39
• RC 43	40
• RC 65	41
• RC 69	42
• RC 70	43
• RC 72	44
• RC 74	45
• RC 77	46

HYBRID ADHESIVES CX80

• HYBRICX premium	47
• HYBRICX 35C	48
• HYBRICX 45S	49
• HYBRICX 70S	50

CLEANING PRODUCTS CX80

• XBRAKE CLEANER	51
• ENGINE CLEANER	52
• ON RUST	53
• CONTACT	54
• JOINTS AND WELDS	55
• FIREPLACES AND GRILLS	56

ANTI-CHIPPING, WELDING PRODUCT CX80

• EASY WELD	57
-------------	----

EPOXY RESINS, SEALANTS CX80

• AUTO WELD cold welding	58
• KWIK WELD cold welding	59
• STIK WELD	60
• SILV WELD	61

OILS

• AGREGICX	62
• DACNICX	63
• PNEUMACX antifreeze	64
• PNEUMACX M	65

CAR PRODUCTS

• STARTING FLUID	66
• FAN BELT SPRAY	67
• MIRROR BOND	68

PROTECTIVE COATINGS

• CYNK SPRAY	69
• ALUCYNK SPRAY	70
• drilling and tapping oil	71



CX80 MULTI-PURPOSE LUBRICANT

The specially formulated multi-purpose product is made from the highest quality raw materials.

- loosens rusted and tilted elements quickly
- cleans and protects equipment from corrosion
- eliminates squeaking and creaking of hinges, locks, curtain rods and other mechanical devices
- improves the function of ignition systems, which are endangered with flooding or humid places
- filters through moisture and forms a protective barrier between the water and the metal
- eliminates moisture-triggered short circuits
- suitable for electronic ignitions
- protects vehicle locks from moisture and freezing
- defrosts locks
- removes dirt, dust, traces of coloured crayons and felt tip pens, chewing gum and adhesives
- 1001 applications in industry, workshops or in the house



package	spray 100 ml	spray 250 ml	duospray 250 ml	spray 500 ml	duospray 500 ml	5 l	25 l	200 l
cardbox (quantity)	24	36	36	24	24	1	1	-
pallet (quantity)	4608	1764	1764	1008	1008	-	-	-
barcode	001	058	075	062	076			





CX80 MULTI-PURPOSE LUBRICANT WITH TEFLON®

An excellent multi-purpose product with exceptional quality of lubrication which can be used in many different industries and in the area of everyday life.

- the result after using is a coat which improves the resistance to abrasion and increases the working life
- the low-friction coefficient characteristic of TEFLON®, leading to high efficiency for electrical connections, structural fittings, military equipment, and in many other areas in which a repetitive movement of the surface is important
- plays a major role in the bicycle industry, ideally suited for the lubrication of chains, gears, brake lines, gears, increases their working life and reduces friction between the elements and their wear and tear
- also suitable as anti-adhesive agent
- can be used in the process for formation of rubber and plastic components, it does not affect the stability and it makes it easier to release from the mould parts

Teflon® is a registered trademark of The Chemours Company FC, LLC. (DuPont), used under license by CX80.



package	spray 100 ml	spray 250 ml	duospray 250 ml	spray 500 ml	duospray 500 ml
cardbox (quantity)	24	36	36	24	24
pallet (quantity)	4608	1764	1764	1008	1008
barcode	007	187	188	193	192





CX80 COPPER GREASE

ANTI-ADHESIVE. Multi-purpose product for use under the most difficult conditions and within high temperature ranges from -30°C up to 1200°C.

PROPERTIES:

- ensures excellent lubrication
- safeguards against attrition, corrosion and high temperatures
- wide temperature range (-30°C to +1200°C)

APPLICATIONS:

- screws and nuts
- threads and all connected surfaces
- fittings
- spark plugs
- wheel and brake discs
- battery terminals
- port installations
- revolving discs
- highly stressed bearings of all kinds
- elements in industrial, construction
- other elements of industrial systems, construction, agricultural and motor vehicles



package	tube 40 g	spray 150 ml	spray 500 ml	duospray 500 ml	can 500 g	5 kg	180 kg
cardbox (quantity)	25	20	12	12	6	1	1
pallet (quantity)	3000	2400	1008	1008	924	-	-
barcode	032	010	065	232	014	128	



519076401600322



519076401600100



519076401600650



519076401602326



519076401600148



519076401601282



CX80 LITHIUM GREASE

Multi-purpose product for the lubrication of industrial, agricultural and motor vehicles' systems. It ensures excellent lubrication even under the toughest conditions.

PROPERTIES:

- resistant to water and oxidation
- protects against attrition and corrosion
- extends life of bearings
- contains EP additives
- mechanically stable and because of its soft consistency, easy to apply
- passes the SKF EMCOR test
- operating temperatures from -20°C up to +130°C



	tube 40 g	spray 150 ml	spray 500 ml	duospray 500 ml	cartridge 400 g	can 500 g	4,5 kg	180 kg
cardbox (quantity)	25	20	12	12	18	6	1	1
pallet (quantity)	3000	2400	1008	1008	1512	924	-	-
barcode	031	013	064	233	286	017	155	



519076401600315



519076401600131



519076401600643



519076401602333



519076401602869



519076401600179



519076401601558



CX80 CERACX GREASE

Multi-purpose calcium grease for very difficult conditions, resistant to water.

PROPERTIES:

- excellent thermal stability – regains its original texture after cooling to ambient temperature
- exceptional resistance to water – consistency does not change even when large amount of water gets through the grease
- does not contain lead or other heavy metals harmful to health and the environment
- brown color
- application temperature from -35°C to +190°C
- viscosity grade NLGI 2

APPLICATION:

- all types of assemblies exposed to high pressures and shock loads, working in conditions where grease is in frequent contact with water (including sea water as it possesses anti-rust properties)
- lubrication of the continuous casting lines
- in steel mills
- bearings in wet and dry places in paper mills (felt cylinders)
- in difficult working conditions (humidity, load, high temperature, dust, etc.)



package	tube 40 g	can 500 g	5 kg	180 kg
cardbox (quantity)	25	6	1	1
pallet (quantity)	3000	924	-	-
barcode	216	210	250	





CX80 MOLYBDENUM GREASE

EASY TO USE GREASE. Multi-purpose product with EP additives molybdenum disulphide and friction modifiers for protection against wear, even under the toughest conditions.

PROPERTIES:

- easy to handle pump mechanism
- high temperature stability
- resistance to moisture
- operating temperature from -25°C up to +150°C

APPLICATIONS:

- vehicles
- forklifts
- industrial equipment working in humid conditions (cranes, gantries, etc.)
- lubricates joints, switches, bearings, shafts and other mechanisms



package	cartridge 400 g	can 500 g	5 kg	180 kg
cardbox (quantity)	18	6	1	-
pallet (quantity)	1512	924	-	-
barcode	287	036	157	





CX80 SILICONE GREASE

SILICONE GREASE FOR PLASTIC AND RUBBER. Colorless lubricant with high viscosity.

PROPERTIES:

- creates a protective film with excellent resistance
- coverage of the friction surfaces with a thin layer of silicone grease leads to an effective reduction of friction and provides a long lasting protection of the equipment
- suitable for use at contact surfaces of plastic, metal, ceramics, rubber, etc.
- does not stain does not adhere to dust
- non-adhesive – facilitates the removal of forms
- operating temperature from -60°C up to +230°C

APPLICATIONS:

- all kinds of sanitary equipment – conventional and lever (gas) valves, seals, connectors, fittings, valves, joints
- clean lubrication of equipment in textile, paper, and food industry
- electrical and power distribution equipment (safety protection of electrical circuits)
- power cases which work under extreme temperatures (from -60°C up to +230°C)
- lubrication of links, locks, hinges screws and sleeves in the automotive industry
- protects against corrosion of printing machines, where the lubricant gets in contact with paper



package	tube 40 g	can 500 g	5 kg	180 kg
cardbox (quantity)	25	6	1	-
pallet (quantity)	3000	924	-	-
barcode	033	020	160	235





CX80 GRAPHITE GREASE

ANTI-SEIZE GREASE. Professional grease with mineral-based calcium with the addition of micronized graphite.

PROPERTIES:

- high resistance to water
- perfect corrosion protection
- high resistance to pressure
- protection against attrition
- excellent adhesion at high temperatures, enables dry lubrication due to property of graphite
- high electrical conductivity
- graphite content: 15%
- operating temperature from -30°C up to +600°C

APPLICATIONS:

- general use (particularly under difficult conditions and high temperature)
- open gearboxes
- construction and agricultural machinery
- chains in stoves (dry lubrication)



package	tube 40 g	cartridge 400 g	can 500 g	5 kg	180 kg
cardbox (quantity)	25	18	6	1	-
pallet (quantity)	3000	1512	924	-	-
barcode	080	285	055	131	254





CX80 BEARING GREASE

HIGH-SPEED BEARINGS LUBRICATION. Complex lithium grease with selected mineral bases and additives (including EP).

PROPERTIES:

- allows application at high temperatures of up to 220°C
- excellent adhesion and water resistance
- very high resistance to aging
- the bearing speed factor of minimum DN 500.000

APPLICATIONS:

- for the lubrication of bearings with high speed, temperature or humidity (mining, automotive and construction machinery, granulators, car vehicles)
- bearings of fans and dryers
- bearings of medium and high number of revolutions
- bearings that are subjected to vibrations



package	tube 40 g	cartridge 400 g	can 500 g	4,5 kg	180 kg
cardbox (quantity)	25	18	6	1	-
pallet (quantity)	3000	1512	924	-	-
barcode	215	288	056	263	276





CX80 WATERPROOF

Multifunctional EP grease provides high load carrying properties, resistance to fresh and salt water, and oxidation and corrosion protection.

PROPERTIES:

- operating temperatures from -30°C up to +600°C
- excellent water resistance- there are no changes in consistency when excessive water penetrates the grease
- excellent anti-oxidation and anti-corrosion properties also in sea water because of addition of natural calcium sulfonate
- does not contain lead or other heavy metals that are hazardous to human health or the environment

APPLICATIONS:

- all greasing points on ship boards and for plain, roller and ball bearings, headsets, shock linkages, swingarm pivots and motorcycle
- other uses in industry and transport
- marine use
- road construction, where a frequent contact with water occurs, for example, in chains, gears of excavators and cranes



	can 500 g	5 kg	180 kg
cardbox (quantity)	6	1	-
pallet (quantity)	924	-	-
barcode	081	134	



519076401600810



519076401601343



CX80 MOTO CHAIN

FOR CHAINS AND OTHER MOTORCYCLE PARTS. Special formulation for motorcycles. Meets specific requirements for lubrication of chains and other moving parts of the motorcycle, such as high rotation and feed rate.

PROPERTIES:

- resistant to dust and dirt
- resistant to water and mud
- transparent – leaves no spots on skin or clothing
- it leaves a long lasting protective layer after drying, which enables a low-noise operation of the chain, and protects against corrosion
- ideal for lubricating locks, exposed fork parts and wherever metal meets metal and friction should be reduced



	spray 150 ml	spray 500 ml
cardbox (quantity)	24	12
pallet (quantity)	2640	1008
barcode	052	219



519076401600520



519076401602197



CX80 WHITE GREASE – SOLID

Penetrates single gaps, forms a lubricating layer that exactly remains where the grease was applied.

PROPERTIES:

- non-hardening
- non-dripping
- non-staining
- does not cause discoloration on the paint
- water and heat resistant
- fights rust and corrosion
- operating temperature from -40°C up to +100°C

APPLICATION:

- long-lasting lubrication on auto hinges, gears, sprockets
- outdoor hinges, latches, overhead door tracks, pulleys
- locks
- cables and guide rails



package	spray 500 ml
cardbox (quantity)	12
pallet (quantity)	1008
barcode	220





CX80 ELECTRICX GREASE

Synthetic oils based grease. Designed for lubrication of any type of machines operating at high temperatures, lightly loaded mechanically. Suitable for applications that require good electrical conductivity.

PROPERTIES:

- outstanding resistance to oxidation, even in the presence of copper and its alloys
- very good cohesion – the oil discharges from the lubricant in very small quantities, even at high temperatures
- effective in sub-zero temperatures

APPLICATION:

- protection against corrosion and oxidation of the terminals, connections points of weight and welding cables
- lubricating stators
- makes dismantling any electrical contacts easier
- lubrication of the mechanical parts under voltage
- lubrication of the windshield wipers



	tube 40 g	can 500 g	180 kg
cardbox (quantity)	25	6	1
pallet (quantity)	3000	924	-
barcode	303	185	



519076401603033



519076401601855



CX80 KERAMICX GREASE

Ceramic grease for screws and connections exposed to high pressure and high temperature.

PROPERTIES:

- suitable for high temperature ranges of (up to 1400°C)
- suitable for use in brake systems with ABS, ASR and ESP, exhaust mounting screws, head collectors and heads and other machine parts
- anti-rust properties
- protects against stainless steel clogging
- water and acids-proof
- does not contain heavy metals that are hazardous to human health or the environment



	tuba 40 g	duospray 500 ml	5 kg	180 kg
cardbox (quantity)	25	24	1	-
pallet (quantity)	3000	1008	-	-
barcode	213	214	227	



5190764016021351



5190764016021421



5190764016022721



CX80 TOWOCX GREASE

Multi purpose, lithium-calcium grease for use in all conditions, especially at high temperatures and where the use of conventional lithium greases is limited.

PROPERTIES:

- meets the requirements of most car manufacturers
- creates a durable layer resistant to moisture, temperature and pollution
- mixable with most conventional lubricants
- does not contain lead or other heavy metals hazardous to health and the environment
- light brown color
- application temperatures from -30°C to +160°C

APPLICATION:

- lubrication of heavily loaded plain, roller and ball bearings, wheel bearings, constant velocity joints, elements of vehicle bodies (hinges, telescopic forks) and gear shock loaded gears
- for general use in industry, where NLGI 2 EP grease is required, resistant to low and high temperatures



	can 500 g	5 kg	180 kg
cardbox (quantity)	6	1	1
pallet (quantity)	924	-	-
barcode	175	260	





CX80 LUBRICANT FOR GATES

Lubricant for garage, sliding and rolling gates. Lubricates, preserves and protects against corrosion. Specially designed formulation for easy and effective maintenance.

PROPERTIES:

- lubricates all moving parts of gates and protects them from moisture and corrosion
- maintains optimal operation in the winter in very low temperatures
- prevents dirt and dust adhesion
- removes squeaking and creaking
- solves hard working mechanisms such as bolts and locks
- unbolts frozen locks

APPLICATION:

- hinges
- fasteners
- chain links
- locks
- hooks
- springs
- shock-absorbing parts
- elements of engines



package	duospray 500 ml
cardbox (quantity)	24
pallet (quantity)	1008
barcode	301





CX80 SILICONE SPRAY

FOR PLASTICS AND RUBBER. Colorless lubricant with high viscosity.

PROPERTIES:

- creates a protective film with excellent resistance
- coverage of the friction surfaces with a thin layer of silicone grease leads to an effective reduction of friction and provides a long-lasting protection of the equipment
- suitable for use at contact surfaces of plastic, metal, ceramics, rubber, etc.
- does not stain does not adhere to dust
- non-adhesive, facilitates the removal of forms
- operating temperatures from -60°C up to $+230^{\circ}\text{C}$

APPLICATION:

- all kinds of sanitary equipment – conventional and lever valves (gas), seals, connectors, fittings, valves, joints
- clean lubrication of equipment in textile, paper, and food industry
- electric and power distribution equipment (assurance of electrical circuits)
- energetic cases which work under extreme temperatures (from -60°C up to $+230^{\circ}\text{C}$)
- in the automotive industry for the lubrication of links, locks, hinges, screws and sleeves
- protects against corrosion by printing machines, where the lubricant gets in contact with paper



package	spray 300 ml	spray 500 ml	duospray 500 ml
cardbox (quantity)	12	12	12
pallet (quantity)	1728	1008	1008
barcode	021	068	237





CX80 PROFESSIONAL SILICONE

High-temperature resistant sealant, resistant to high (+380°C) and low temperatures (-65°C). Elastic, fast curing sealant that forms lasting, not shrinking and UV-resistant filling compound. Seals and glues most surfaces such as glass, ceramics, aluminum and metal perfectly.

APPLICATION:

- machines and heating equipment
- fireplaces
- engines and other mechanical parts that are exposed to high temperatures
- fireplaces, stacks and vents

TECHNICAL DATA:

- curing time: 3 mm/24 h
- tooling time: 10-20 min
- operating temperature from -60°C up to +230°C
- applying temperature from +5°C up to +40°C
- crosslinking: acetoxy



package	tube 70 ml	tube 70 ml	applicator 250 g	applicator 250 g	cartouche 310 ml	cartouche 310 ml	cartouche 310 ml	cartouche 310 ml
cardbox (quantity)	50	50	12	12	24	24	24	24
pallet (quantity)	5500	5500	1440	1440	2016	2016	2016	2016
barcode	109	061	139	140	304	034	063	297



red



black



red



black



transparent



red



black



transparent



CX80 PROFESSIONAL ECO SILICONE

SEALANT. One-component, flexible (enhances load bearing & shock absorbing characteristics of the bond area), sticky paste in gray with very good adhesion to rough surfaces.

PROPERTIES:

- does not contain toxic solvents
- non-corrosive
- oils, gasoline, greases resistant

APPLICATION:

- general use
- automotive industry (crankcases, timing covers, cylinder heads, oil pans, gear boxes, water pumps, thermostats)
- can be used instead of permanent seals

TECHNICAL DATA:

- curing time: 3 mm/24 h
- tooling time: 10-20 min
- operating temperature from -60°C up to +230°C
- applying temperature from +5°C up to +40°C
- crosslinking: neutral



	applicator 250 g	cartouche 310 ml
cardbox (quantity)	12	24
pallet (quantity)	1440	2016
barcode	197	298



gray



gray



CX80 SANITARY SILICONE

Fast-curing sanitary silicone with high resistance to moisture, mold and mildew.

PROPERTIES:

- long-term moisture, mold and mildew resistance
- durable, flexible, waterproof seal
- no staining of porous substrates
- skin formation time – approx. 7 min
- curing time – 3 mm/18 h

APPLICATION:

- suitable for use in bathrooms, kitchens and cold rooms (bathtubs, shower trays and shower enclosures also acrylic and PVC, washbasins and sinks with conglomerate and natural stone tops)
- common wet-area building materials
- glass works



package	applicator 250 g	applicator 250 g
cardbox (quantity)	12	12
pallet (quantity)	1440	1440
barcode	205	204



white



transparent



CX80 SUPERFAST SANITARY SILICONE

Ultimate fast-curing sanitary silicone with high resistance to moisture, mold and mildew.

PROPERTIES:

- long-term moisture, mold and mildew resistance
- durable, flexible, waterproof seal
- no staining of porous substrates
- skin formation time – approx. 5 min
- curing time – 3 mm/18 h

APPLICATION:

- suitable for use in bathrooms, kitchens and cold rooms (bathtubs, shower trays and shower enclosures also acrylic and PVC, washbasins and sinks)
- common wet area building materials
- glass works
- **THIS PRODUCT IS NOT RECOMMENDED FOR:** polyethylene, polypropylene, teflon and natural stone



package	applicator 250 g	applicator 250 g
cardbox (quantity)	12	12
pallet (quantity)	1440	1440
barcode	208	203



white



transparent



CX80 MULTI-PURPOSE SILICONE

For filling, gluing, pointing and grouting of ceramic and glass elements and certain metals.

PROPERTIES:

- excellent adhesion to porous – concrete, stone, masonry, brick, wood and non-porous substrates – glass, ceramics and glazed surfaces
- durable, flexible, waterproof seal
- skin formation time – approx. 5 min
- the rate of curing – 3 mm/18 h

APPLICATION:

- perfect for workshops and building works
- grouting tiles both indoors and outdoors
- ventilation systems
- refrigerating systems



	applicator 250 g	applicator 250 g	cartouche 310 ml	cartouche 310 ml
cardbox (quantity)	12	12	24	24
pallet (quantity)	1440	1440	2016	2016
barcode	207	206	172	171



white



transparent



white



transparent



CX80 BUILDING-PURPOSES SILICONE

For pointing and grouting of typical building materials – including most plastics.

PROPERTIES:

- long-term moisture, mold and mildew and UV resistance
- excellent adhesion to porous – concrete, stone, masonry, brick, wood (including painted with acrylic paints) and non-porous substrates – glass, ceramics and glazed surfaces, metals (including aluminum), plastics (PVC), acrylic and polycarbonate
- durable, flexible, waterproof seal
- non-corrosive
- no staining of porous substrates
- skin formation time – approx. 5 min
- curing time – 3 mm/18 h

APPLICATION:

- where flexible, atmospheric conditions resistant sealing needed
- pointing window frames and doors,
- molding walls, partitions, polycarbonate and acrylic roofs
- glass works



package	applicator 250 g	applicator 250 g
cardbox (quantity)	12	12
pallet (quantity)	1440	1440
barcode	201	200



white



transparent



CX80 NEUTRAL SILICONE

For pointing and grouting of typical building materials – including most plastics.

PROPERTIES:

- long-term moisture, mold and mildew and UV resistance
- excellent adhesion to porous – concrete, stone, masonry, brick, wood (including painted with acrylic paints) and non-porous substrates – glass, ceramics and glazed surfaces, metals (including aluminum), plastics (PVC), acrylic and polycarbonate
- durable, flexible, waterproof seal
- non-corrosive
- no staining of porous substrates
- skin formation time – approx. 5 min
- curing time – 3 mm/18 h

APPLICATION:

- where flexible, atmospheric conditions resistant sealing needed
- pointing window frames and doors
- molding walls, partitions, polycarbonate and acrylic roofs
- glass works



package	applicator 250 g	applicator 250 g
cardbox (quantity)	12	12
pallet (quantity)	1440	1440
barcode	199	202



white



transparent



CX80 FIREPLACE SEALANT

Based on water glass, designed for repairs in places exposed to extremely high temperatures (fireplaces, stoves, grates).

PROPERTIES:

- operating temperatures up to +1250°C (stays up to +1500°C for a short time)
- water glass based – increases gas-tightness
- easy application
- does not shrink or expand
- resistant to weather changes, UV and aging effects
- excellent adhesion to metal brick and cement

APPLICATION:

- applying ceramic tiles to the fireplace surround or heat shielding behind the stove
- fireplaces, ovens, grills
- elements exposed to fire



package	cartouche 300 ml
cardbox (quantity)	24
pallet (quantity)	2304
barcode	070



black



CX80 BONDICX 01

Instant one-part, room-temperature curing cyanoacrylate adhesive with low viscosity and high strength.

APPLICATION:

- rubber
- polystyrene
- wood
- metal
- plastics
- around-the-home use



	bottle 20 g	bottle 50 g
cardbox (quantity)	10	10
pallet (quantity)	-	-
barcode	083	198





CX80 BONDICX 06

One-component, fast curing cyanoacrylate adhesive with low viscosity for plastic and rubber.

APPLICATION:

- rubber parts (EPDM, NBR)
- polyethylene
- polypropylene
- PTFE (Teflon)
- fluorine rubber (silicone)



	bottle 20 g	bottle 50 g
cardbox (quantity)	10	10
pallet (quantity)	-	-
barcode	085	209





CX80 BONDICX 05

General purpose cyanoacrylate adhesive in non-clogging bottle.

APPLICATION:

- porcelain
- metal
- wood
- ceramics
- rubber
- leather
- textile



package	bottle 5 g
cardbox (quantity)	24
pallet (quantity)	1680
barcode	011





CX80 BONDICX 96

Cyanoacrylate adhesive with low viscosity for repairing small, metal areas.

APPLICATION:

- where penetration of the adhesive is required (steel, aluminum, zinc dichromate, nitrile rubber, neoprene, polycarbonates, phenolic and ABS materials)



package	bottle 20 g
cardbox (quantity)	10
pallet (quantity)	-
barcode	137





CX80 BONDICX 20

Ethyl-cyanoacrylate adhesive with low viscosity for small plastic and rubber areas.

APPLICATION:

- where penetration of the adhesive is required (nitrile rubber, neoprene, polycarbonates, phenolic materials, steel, aluminum, zinc dichromate)



package	bottle 20 g
cardbox (quantity)	10
pallet (quantity)	-
barcode	125





CX80 BONDICX GEL

General purpose cyanoacrylate adhesive gel with high viscosity and high strength.

PROPERTIES:

- fast curing
- non-dripping
- perfect for porous materials or when controlling adhesive flow is critical

APPLICATION:

- metal
- plastic
- leather
- paper
- cardboard
- wood
- cork
- foam



	tube 3 g	tube 20 g
cardbox (quantity)	90	20
pallet (quantity)	8100	-
barcode	138	136





CX80 BONDICX 48

One-component cyanoacrylate adhesive with medium viscosity and high elasticity.

APPLICATION:

- wide range of metal, plastics and elastomers
- ideal for bonding rubber to metal, stainless steel and galvanized sheet
- mounting small, plastic gears on metal shafts
- bonding rubber O-rings to the metal parts
- installation of rubber seals



package	bottle 50 g
cardbox (quantity)	10
pallet (quantity)	-
barcode	126





CX80 BONDICX 60

General purpose cyanoacrylate adhesive perfect for bonding rubber to plastic, plastic to plastic and rubber to rubber.

APPLICATION:

- fast curing of any bonding elements
- high strength



package	bottle 5 g
cardbox (quantity)	10
pallet (quantity)	-
barcode	100





CX80 RC 20G

Anaerobic adhesive for mounting cylindrical parts ensuring high strength. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- **resistance to high temperatures**
- high durability, even in the case of loose or worn parts that require more fill slots
- protection against corrosion
- resistance to vibration
- improves the uniform distribution of stress
- initial binding to 15 minutes
- full strength after 24 hours
- temperature resistance from -55°C to +230°C

APPLICATION:

- permanent bonding and protection of cylindrical fitting parts, where high temperature resistance is required



package	bottle 50 ml
cardbox (quantity)	10
pallet (quantity)	-
barcode	113





CX80 RC 22

Anaerobic adhesive for securing metal threaded connections with low strength bonding. Binding in contact with metal surfaces in the absence of air.

PROPERTIES:

- low strength
- initial binding up to 15 minutes
- full strength: steel – after 6 hours, stainless steel – after 24 hours, brass – after 1 hour
- temperature resistance from -55°C to +150°C

APPLICATION:

- sealing and protection against self-loosening bolts with low resistance, threading, screws, adjustment screws, bolts fastening flanges, pulleys which could break during disassembly, eg. aluminum or copper



package	bottle 10 ml	bottle 50 ml	bottle 250 ml
cardbox (quantity)	10	10	10
pallet (quantity)	-	-	-
barcode	114	082	115



519076401601145



519076401600827



519076401601152



CX80 RC 38

Anaerobic adhesive for mounting cylindrical parts providing high strength. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- high strength
- protection against corrosion
- resistance to vibration
- improves the uniform distribution of stress
- initial binding up to 15 minutes
- full strength after 24 hours
- temperature resistance from -55°C to +150°C

APPLICATION:

- permanent binding and protection of rotating components
- assembly of steel bearings, wheels, gears, pulleys, sprockets



package	bottle 10 ml	bottle 50 ml	bottle 250 ml
cardbox (quantity)	10	10	10
pallet (quantity)	-	-	-
barcode	037	084	118



519076401600377



519076401600841



519076401601183



CX80 RC 41

Anaerobic adhesive for fastening cylindrical parts with medium binding strength. It binds when in contact with metal surfaces and in isolation from oxygen.

PROPERTIES:

- very high binding strength
- medium level of disassembly characteristics
- protection against corrosion
- resistance to vibration
- secured against self-unscrewing
- initial binding of up to 15 minutes
- full strength after 24 hours
- temperature resistance from -55°C to +150°C

APPLICATION:

- fastening cylindrical and concentric joints
- fastening of bearings on shafts and castings
- particularly recommended in cases of later disassembly for maintenance purposes



package	bottle 50 ml
cardbox (quantity)	10
pallet (quantity)	-
barcode	239





CX80 RC 72

Anaerobic adhesive for securing metal thread joints with very high binding strength. It binds when in contact with metal surfaces and in isolation from oxygen.

PROPERTIES:

- high binding strength
- protection against corrosion
- resistance to vibration
- safeguarding against thread leakages
- resistance to high temperatures
- initial binding to 15 minutes
- full strength after 24 hours
- temperature resistance from -55°C to +230°C

APPLICATION:

- permanent blocking of nuts and bolts
- sealing
- securing threads against self-unscrewing during vibrations
- recommended particularly for small-size threads (thread diameter of up to M80)



package	bottle 50 ml
cardbox (quantity)	10
pallet (quantity)	-
barcode	241





CX80 RC 42

Anaerobic adhesive for securing metal threaded connections with medium strength binding. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- medium strength
- protection against corrosion
- resistance to vibration
- preventing leakage of thread
- increasing the force and slip for easy installation
- initial binding to 15 minutes
- full strength after 24 hours
- temperature resistance from -55°C to +150°C
- disassembly with manual tools

APPLICATION:

- locking nuts and bolts
- sealing
- protects threads against loosening during vibration
- recommended for small thread (the thread diameter up to M25)



package	bottle 10 ml	bottle 50 ml	bottle 250 ml
cardbox (quantity)	10	10	10
pallet (quantity)	-	-	-
barcode	038	086	119





CX80 RC 43

Anaerobic adhesive for securing metal threaded connections with medium strength bonding. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- medium strength
- protection against corrosion
- resistance to vibration
- preventing leakage of thread
- increasing the force and slip for easy installation
- initial binding to 15 minutes
- full strength after 24 hours
- temperature resistance from -55°C to +150°C
- disassembly with manual tools

APPLICATION:

- locking nuts and bolts
- sealing
- protects threads against loosening during vibration
- recommended for small thread (the thread diameter up to M36)



package	bottle 10 ml	bottle 50 ml	bottle 250 ml
cardbox (quantity)	10	10	10
pallet (quantity)	-	-	-
barcode	087		119



519076401600872



519076401601206



519076401601190



CX80 RC 65

Anaerobic sealant for pipe threads with low strength. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- low strength for easy disassembly
- protection against corrosion
- resistance to vibration
- preventing leakage of thread
- increasing the force and slip for easy installation
- initial binding to 2 hours
- full strength after 24 hours
- seal until the burst pressure (10 000 psi)
- instant (after 20 minutes) pre-seal (up to 2 bar)
- resistant to temperatures from -55°C to +150°

APPLICATION:

- locking and sealing pipe threads with a diameter of 15 to 80 mm
- protects threads against loosening during vibration
- recommended for metal threads



package	bottle 50 ml
cardbox (quantity)	10
pallet (quantity)	-
barcode	122





CX80 RC 69

Anaerobic sealant for metal threads with medium strength. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- medium strength
- protection against corrosion
- initial binding to 2 hours
- full strength after 24 hours
- seal until the burst pressure (10 000 psi)
- instant (after 20 minutes) pre-seal (up to 2 bar)
- resistant to temperature from -55°C to +150°C

APPLICATION:

- blocking and sealing pipe threads
- protects threads against loosening during vibration



	bottle 10 ml	bottle 50 ml	bottle 250 ml
cardbox (quantity)	10	10	10
pallet (quantity)	-	-	-
barcode	112	116	117



5190764016011211



5190764016011691



5190764016011761



CX80 RC 70

Anaerobic adhesive for securing metal threaded joints with very high bonding strength. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- high strength
- protection against corrosion
- resistance to vibration
- increasing pressure and slip for easy installation
- resistance to oiling
- initial binding to 15 minutes
- full strength after 24 hours
- resistant to temperatures from -55°C to +150°C

APPLICATION:

- permanent locking of nuts and bolts
- sealing
- securing threads against loosening during vibration
- recommended for small thread (the thread diameter up to M20)



package	bottle 10 ml	bottle 50 ml	bottle 250 ml
cardbox (quantity)	10	10	10
pallet (quantity)	-	-	-
barcode	039	090	121



519076401600391



519076401600902



519076401601213



CX80 RC 74

Anaerobic sealant for flat surfaces with medium strength. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- medium strength
- resistance to oil, water and glycol
- protection against corrosion
- initial binding to 20 minutes
- full strength after 24 hours
- seal until the burst pressure (10 000 psi)
- instant (after 20 minutes) pre-seal (up to 0.5 bar)
- resistant to temperature from -55°C to +150°C

APPLICATION:

- sealing of tightly fitting metal surfaces



package	bottle 50 ml
cardbox (quantity)	10
pallet (quantity)	-
barcode	123





CX80 RC 77

Anaerobic sealant for pipes from 3/4" to 3" with low strength. Remains liquid until isolated from oxygen in the presence of metal ions.

PROPERTIES:

- low strength
- resistant to oil, water, fuel, hydraulic fluids
- shear strength on steel : 11 N/mm²
- initial binding: steel – after 25 minutes, stainless steel – 4.5 hours, brass – 15 minutes
- full strength: steel – after 6 hours, stainless steel – after 36 hours, brass – after 1 hour
- temperature resistance from -55°C to +150°C

APPLICATION:

- protection against leakage of liquids and gases in metal installations



	bottle 50 ml	bottle 250 ml
package		
cardbox (quantity)	10	10
pallet (quantity)	-	-
barcode	123	



519076401601237



519076401602586



CX80 HYBRICX PREMIUM

General purpose adhesive with a high modulus of viscosity and high penetration capacity. One-component adhesive does not react with the surface, curing at room temperature, used for the installation of a high strength joint.

PROPERTIES:

- ready to use
- hybrid technology (combines the best properties of silicone sealants and polyurethane adhesives)
- cures in contact with moisture
- high strength bonding
- consistency prevents adhesive flow
- completely odorless and solvent-free
- perfect smooth and porous surfaces
- excellent adhesion without primer
- can be painted and sandblasted

APPLICATION:

- bonds almost all areas – ceramics, wood, metals, plastics, concrete etc.
- elements exposed to difficult operating conditions (eg. sealing natural stone)
- fastening elements exposed to vibrations and high speed



package	applicator 250 g	applicator 250 g	cartouche 290 ml
cardbox (quantity)	12	12	24
pallet (quantity)	1440	1440	2016
barcode	141	279	026



white



black



white



CX80 HYBRICX 35C

Fast-curing and high strength adhesive. Combines, adhesives and seals all possible surfaces.

PROPERTIES:

- cures at room temperature in contact with moisture
- creates solid, flexible joint
- solvent-free
- does not contain phthalates
- does not contain tin compounds
- odorless
- easy to process at temperatures from +5°C to +40°C
- stable at temperatures from -40°C to +100°C
- crystal clear
- resistant to yellowing
- corrosion-resistant
- high strength bonding on a variety of substrates

APPLICATION:

- perfect for invisible bonding where bond strength of a structural adhesive and curing speed of an instant adhesive is needed
- bonding various materials, such as: glass, plexiglass, wood, metals, transparent decorations, plastic or natural stone



package	applicator 250 g
cardbox (quantity)	12
pallet (quantity)	1440
barcode	142



transparent



CX80 HYBRICX 45S

Fast-curing and high strength adhesive. Combines, adhesives and seals all possible surfaces.

PROPERTIES:

- cures at ambient temperature in contact with moisture creating a solid, flexible joint
- universal
- suitable for bonding a wide variety of surfaces
- solvent-free
- does not contain isocyanates
- does not contain phthalates
- odorless
- easy to process at temperatures of +5°C to +40°C
- stable at temperatures from -40°C to +100°C
- corrosion-resistant
- creates a flexible joint after curing
- can be painted

APPLICATION:

- perfect for bonding where instant curing of an adhesive is needed
- bonding various materials, such as: wood, glass, metals, plastics and mineral surfaces
- perfect for mirror installation



package	applicator 250 g
cardbox (quantity)	12
pallet (quantity)	1440
barcode	143



519076401601435



CX80 HYBRICX 70S

Fast-curing and high strength adhesive. Combines, adhesives and seals all possible surfaces.

PROPERTIES:

- cures at room temperature in contact with moisture
- creates solid, flexible joint
- high strength bonding on a variety of substrates (wet and without any primer)
- solvent-free
- does not contain isocyanates
- does not contain phthalates
- does not contain tin and lead compounds
- does not contain plasticizers
- odorless
- easy to process at temperatures of +5°C to +50°C
- stable at temperatures from -40°C to +100°C
- instant curing
- water-resistant
- corrosion-resistant
- creates a flexible joint after curing
- can be painted and polished
- resistant to acids, alkalis, mineral oils and solvents
- cure time: 3 minutes

APPLICATION:

- connects, secures, seals and fills many materials, such as wood, glass, metals, plastics and mineral substrates
- glues frames, decorative moldings, cables, panels (siding)
- useful for every handyman



package	applicator 250 g
cardbox (quantity)	12
pallet (quantity)	1440
barcode	225



519076401602258



CX80 XBRAKE CLEANER

Instant spray for cleaning brakes.

PROPERTIES:

- removes all sediments from asphalt and tar, dust from brake pads wear and baked-on dirt
- eliminates brakes squeal
- leaves no traces
- removes brake fluid, oil and grease
- makes rapid repair and fitting of parts easier
- does not contain chlorinated solvents
- degreases

APPLICATION:

- cleaning working parts of the braking system
- can be used for cleaning carburetors and throttle (won't get into the engine or the injection system)



package	spray 500 ml	51	251	2001
cardbox (quantity)	12	1	1	-
pallet (quantity)	1008	-	-	-
barcode	218	249	242	



519076401602180



519076401602494



519076401602425



CX80 ENGINE CLEANER

Car engine cleaner.

PROPERTIES:

- contains additives that easily dissolve burnt oil, car grease, stains of petrol and any dried dirt
- safe for electronics, ECU (computer) and electrical wiring
- does not contain dissociated ions
- low electrical conductivity
- does not leave salty layer

APPLICATION:

- exterior cleaning of car engines
- specially designed for modern TDI engines, TDCi, CDTi, JTDm



package	atomizer 600 ml	5 l
cardbox (quantity)	12	1
pallet (quantity)	660	-
barcode	049	135



5190764016004901



5190764016013501



CX80 ON RUST

Rapid, high-performance rust remover.

PROPERTIES:

- removes rust either in the free and bound scale protects against corrosion
- displaces the water penetrates into the gap, e.g., merging plates welded and crimped
- fast, long-lasting and easy to maintain even heavily corroded parts

APPLICATION:

- anti-corrosion protection of any metal conjunction
- hard-metal connections, for example: thresholds, wheel chassis components removal and neutralization of corrosion



package	duospray 500 ml
cardbox (quantity)	24
pallet (quantity)	1008
barcode	217





CX80 CONTACTX

Cleaning and dissolving spray, for the electronics and electrical engineering.

PROPERTIES:

- removes grease, dirt, old lubricants and oils, silicones, sulphides, oxides and any soldering residue

APPLICATION:

- cleaning of printing plates directly after the installation of the elements
- removal of scratching and creaking noises with potentiometers
- cable and edge connection where the maximum reduction of resistance is required (Installation of computers, high-end, welding)



package	spray 500 ml
cardbox (quantity)	12
pallet (quantity)	1008
barcode	222





CX80 JOINTS AND WELDS

Cleaner for bathroom joints.

PROPERTIES:

- cleans
- disinfects
- removes black marks
- bleaches

APPLICATION:

- bathrooms, toilets, kitchens
- trays, bathtubs, sinks, toilet bowls and toilet boards
- walls and floors in damp rooms
- ceramic, acrylic, rubber, silicone joints and welds
- shower curtains
- synthetic resin surfaces



package	atomizer 600 ml
cardbox (quantity)	12
pallet (quantity)	660
barcode	280





CX80 FIREPLACES AND GRILLS

Cleaner for fireplaces, ovens and grills.

PROPERTIES:

- thoroughly removes dirt, soot and black streaks
- perfectly cleans burnt fat
- can be applied to surfaces in contact with food

APPLICATION:

- cleaning and degreasing grills, ovens, hobs (also ceramic) and accessories
- cleaning windows, stone and bricks in fireplaces



package	atomizer 600 ml
cardbox (quantity)	12
pallet (quantity)	660
barcode	281





CX80 EASY WELD

Anti-chipping, welding product.

PROPERTIES:

- reduces adhesion of metal fragments
- improves welding efficiency
- silicone-free

APPLICATION:

- protects nozzles, tools and surfaces from fusing metal splinters by electric while welding (MIG/MAG)



package	spray 500 ml
cardbox (quantity)	12
pallet (quantity)	1008
barcode	221





CX80 AUTO WELD. COLD WELDING.

Two-component epoxy resin to bind all hard surfaces.

PROPERTIES:

- creates a resistant joint
- useful wherever you need to glue or fill surfaces
- fixes all hard surfaces, such as metal, steel, iron, aluminium, brass, copper, zinc, wood, porcelain and plastic
- glues and repairs damaged pipes, fuel tanks, batteries, cylinder heads, engine blocks
- can be drilled, sanded, milled, threaded and painted
- it can withstand temperatures up to 315°C
- durability in tube – 25 years



package	tubes 2x27g
cardbox (quantity)	30
pallet (quantity)	2100
barcode	009





CX80 KWIK WELD. COLD WELDING.

Quick-drying two-component epoxy adhesive for all hard surfaces.

PROPERTIES:

- creates a resistant joint
- can be shaped to 4 minutes after application
- glues, fills, fixes all hard surfaces, such as: metals, steel, iron, aluminium, brass, copper, zinc, wood, porcelain and plastic
- can be drilled, sanded, milled, threaded and painted
- withstand temperatures up to 150°C
- durability in tubes – 25 years

APPLICATION:

- bonding and repairing of cracked engine blocks, jacks and valve guides, pulleys, alternators and starters, cut down drains, bridges and hubs, cracks and leaks, leaky boilers, refrigeration units, ovens parts, bathrooms equipment, tiles ceramic pipes for hot and cold water, screws, bolts and dowels, washing machines, dryers, lawnmowers etc.



package	tubes 2x27g
cardbox (quantity)	30
pallet (quantity)	2100
barcode	012





CX80 STIK WELD

Two-component epoxy sealant reinforced with steel.

PROPERTIES:

- joins, fixes, seals (also under water)
- ideal for emergency and quick repairs
- fixes all hard surfaces, such as metal, steel, iron, aluminium, brass, copper, zinc, wood, porcelain and plastic, batteries, fuel tanks, cylinders, cast gears and pumps, cylinder heads and many others
- can be drilled, sanded, milled, threaded and painted (its consistency eliminates leakage)
- stainless steel, unshrinkable, non-toxic
- resistance to temperatures up to +150°C



package	tube 60 g
cardbox (quantity)	18
pallet (quantity)	1260
barcode	022





CX80 SILVWELD

Two-component, transparent epoxy adhesive for general use.

PROPERTIES:

- easy application
- fixes after mixing the two components
- high strength
- moisture resistant
- due to the long time shelf life and medium viscosity adhesive is ideal for large surfaces and where long period of time is required to set the parts to be bonded
- perfect for all types of metal, ceramics, wood, glass, rigid plastics and many others
- withstands temperatures up to 150°C



package	applicator 24 ml
cardbox (quantity)	24
pallet (quantity)	2160
barcode	079





CX80 AGREGICX

Mineral oil for lawnmowers and aggregates.

PROPERTIES:

- protects against wear and corrosion
- keeps the engine free of residue and carbon deposits
- provides good lubrication
- can be used at any temperature

APPLICATION:

- four-stroke and diesel internal combustion engines (including out-board), lawnmowers, generators, lawn tractors, brushcutters, pumps, snowblower, compactors, etc.



package	bottle 600 ml
cardbox (quantity)	12
pallet (quantity)	660
barcode	181





CX80 DACNICX

Mineral oil for air compressors.

PROPERTIES:

- protects against wear and corrosion
- prevents the formation of residue and carbon deposits
- provides good separation of mixtures oil-to-air and oil-condensate
- optimizing compressor efficiency, thereby reducing operation costs
- extending life of filter elements
- prevents clogging of filters
- withstands temperatures up to 100°C

APPLICATION:

- lubrication of the screw (rotary) and piston air compressors



package	bottle 600 ml
cardbox (quantity)	12
pallet (quantity)	660
barcode	179





CX80 PNEUMACX ANTIFREEZE

Synthetic oil for pneumatic tools.

PROPERTIES:

- prevents wear and extends tool life
- impact resistant
- contains high-quality EP additives
- ensures work equipment at low temperatures
- protects against wear and corrosion
- removes water
- prevents the formation of ice at air outlet
- does not miscible with conventional mineral oils
- low pour point temperature
- temperature resistance to -50°C

APPLICATION:

- lubrication of pneumatic tools, high-performance drills
- suitable for spraying pneumatic systems



package	bottle 600 ml
cardbox (quantity)	12
pallet (quantity)	660
barcode	177





CX80 PNEUMACX M

Mineral oil for pneumatic tools.

PROPERTIES:

- prevents wear and extends tool life
- impact resistant
- contains high-quality EP additives
- ensures work equipment at low temperatures
- protects against wear and corrosion
- removes water
- prevents the formation of ice at air outlet
- does not miscible with conventional mineral oils
- low pour point temperature
- temperature resistance to -50°C

APPLICATION:

- lubrication of pneumatic tools, high-performance drills
- suitable for spraying pneumatic systems



package	bottle 600 ml
cardbox (quantity)	12
pallet (quantity)	660
barcode	178



519076401601787



CX80 STARTING FLUID

Makes starting petrol and diesel engines at low temperatures easier.

PROPERTIES:

- causes rapid engine start, extending life of the starter and the battery
- contains an additive that lubricates upper part of the cylinder, in order to minimize the consumption of the engine failed starts
- effective up to -50°C
- aerosol fits all standard brackets injectors

APPLICATION:

- in passenger cars, trucks, buses, construction and agricultural machinery, boats, airplanes, mining equipment



package	spray 500 ml
cardbox (quantity)	24
pallet (quantity)	1008
barcode	278





CX80 FAN BELT SPRAY

Applicable for all types of drive belts and suitable for its strengthening and securing it against slippages caused by heat, cold, humidity or presence of liquids.

PROPERTIES:

- easy to use
- suitable for all types of belts
- preserves its softness, does not harden
- protects the belt against aging
- hinders humidity and therefore safeguards against cracks and premature wear and tear
- increases friction, securing the belt against slippage

APPLICATIONS:

- for fan and flat belts, made of rubber, leather or fabric
- particularly suitable for all types of conveyer belts in auto vehicles, lorries/trucks, busses and ship engines, agricultural equipment, in air-conditioning equipment and industry-used drive belts.



package	spray 500 ml
cardbox (quantity)	24
pallet (quantity)	1008
barcode	278



519076401603118



CX80 MIRROR BOND

Adhesive for bonding and mounting reverse mirror to the windscreen.

PROPERTIES:

- rapid and durable bond
- perfect for self-assembly



package	applicator 2 g
cardbox (quantity)	10
pallet (quantity)	-
barcode	048





CX80 ZINC SPRAY

Quick-drying spray providing protection against corrosion.

PROPERTIES:

- electrically conductive, allowing electric welding of coated surface
- excellent adhesion
- creates a smooth, protective coating for all types of paint
- perfect as a primer for surfaces exposed to moisture
- resistant to high temperatures (may be used from 15°C to 30°C; however, the most effective protection against corrosion occurs at the temperature above 20°C – the air contains less moisture)
- can be painted after drying
- the content of zinc in the dry film up to 90%

APPLICATION:

- corrosion protection of standard exhaust pipes, elements of car body and chassis and all kinds of pipe systems and steel structures



package	spray 500 ml
cardbox (quantity)	24
pallet (quantity)	1008
barcode	278





CX80 ALUCYNK SPRAY

Fast-dry anticorrosive.

PROPERTIES:

- high content of zinc and aluminium: 99%
- high anti-abrasion and atmospheric conditions
- perfect coverage
- very efficient and easy to use
- resistance to high temperatures (up to 490° zC)
- **short dry-time**
- based on acrylic resin
- silver color

APPLICATIONS:

- long-lasting protection of metal surfaces against corrosion
- mending the broken zinc elements i.e. gutter, roofs, fences and pipes
- mending the cut, heat-fastened, and welded elements
- after zinc, heat-fastening and welding corrections



package	spray 500 ml
cardbox (quantity)	24
pallet (quantity)	1008
barcode	278





CX80 DRILLING AND TAPPING OIL

Oil for cutting ferrous and non-ferrous metals.

PROPERTIES:

- very good anti-wear and EP properties
- prolongs tool life
- prevents from microroughness
- provides very good surface finish (helps reducing production costs)
- very good behaviour on a large scale of cutting parameters
- low treatment cost (ecological cooling liquid)
- low mist oil formation which improves work conditions

APPLICATION:

- machining of hard and very hard steels (bearing steels), especially heat-resistant steel (NIMONIC and VASPALLOY) and titanium alloys (aviation and medical applications)
- can also be used for low carbon steel and copper alloy
- turning, threading, milling, cutting, deep drilling



package	spray 500 ml
cardbox (quantity)	12
pallet (quantity)	1008
barcode	282



www.cx80.pl